

Stripit Kit®



Using High Efficacy LEDs and power supplies, RedBird LED is proud to offer our newest LED retrofit, the **Stripit Kit® CORE® System**. Easy and quick to install, and covered by **10 Year Full Replacement Warranty**. Priced affordably and with efficacy levels of 190 lm/w the Stripit Kits' cost per lumen is one of the lowest in the industry. A snap-on Polycarbonate diffuser or clear lens is included with each strip.

Exceptional Thermal Management enabled via a permanent direct molecular fusing between the aluminum core PCB carrying the LEDs and the custom aluminum extrusion. This proprietary design feature delivers the **Lowest In-Situ Temperature levels** in the industry and a robust mechanical configuration. Based on our **LM80 and the ISTMT data**, the Energy Star TM-21 Lifetime **exceeds a million hours**.

RedBird's multi-volt (90-305 VAC) LED drivers provide active power factor correction and a discontinuous-current-mode of operation. Built with premium components, the Drivers operate at **92% Efficiency Levels**, PF=0.996; THD < 6%, and with an **MTBF Life Expectancy > 140,000 hours**. Continuous dimming and dim-to-off is available via the 0-10V control signal. Power options for the Constant Current Drivers range from 9 to 190 watts.

Built in the USA

with 100,000 hour lifetime and Ten Year Full System Replacement Warranty With these levels of quality, efficiency and cool operating temperatures we are able to provide a comprehensive ten year full replacement warranty with no pro-rating or exhaustive list of exclusions. Most orders ship from Stock.

RedBird LED

4020 Steve Reynolds BLVD
Duluth, GA 30093
678-RED-BIRD (733-2473)
www.redbirdled.com
info@redbirdled.com
j.eppstein@redbirdled.com

09-08-2025



6 Quick Steps to Retrofit:

- ◆ **Remove exiting tubes, ballast (and tombstone terminals if desired)**
- ◆ **Connect driver output wires to the WAGO connector on the LED Strips**
- ◆ **Snap-on Diffuser or Lens to the LED Strips**
- ◆ **Mount LED Driver in Fixture**
- ◆ **Position LED Strips and fasten to fixture with self-drilling TEK-Screws provided**
- ◆ **Connect input power, turn on your upgraded Lights and enjoy!**

Fast and Easy Installation, only one tool required

The complete system has been designed to cut installation time and complexity to an absolute minimum. Freedom to locate the LED strips and the driver within the fixture allows optimizing the fit for each application. The installer simply positions strips as desired and mounts them with using provided TEK-Screws with a cordless 1/4" nut driver. This provides a positive mechanical attachment while the aluminum extrusion guarantees excellent thermal management regardless of any discontinuities in the fixture's mounting surface. No messy thermal grease, tapes or foam pads are required.

Low-profile Extrusions-Lens/Diffuser allow placement in close quarters. Compatible with wide array of fixtures including drop-in troffers, cove-lighting, wraps, signage, backlit panels, display case lighting, reach-in coolers and more. cULus listed for field installation as a retrofit product.



Check the DLC QPL to view Stripit Kit Models at <http://designlights.org/qpl>

Stripit Kit®

11-29-2018

Stripit Kit® SPECIFICATIONS AND FEATURES	
Dimensions	2' Strips 21.5" L X 0.88" W X 0.55" H 4' Strips 44.0" L X 0.88" W X 0.55" H
Standard CCTs	3500K, 4100K, 5000K
CCT Tolerance	3 McAdam Ellipse Range
CRI	> 85
R9	> 10
D _{uv}	<0.002
Driver Input Voltage	90-305 VAC; 50-60 Hz Standard; 347- 480 VAC available
Driver Power Levels	9, 12, 14, 18, 22, 28, 36, 44, 95 Watts
Power Factor	0.999 at 120 VAC; 0.967 at 277 VAC
THD	< 8%up
Driver Efficiency	to 92%
Dimming Option	0 -10 Volt Continuous dimming from 100% to < 10% Dim to Zero available
Sensor Compatibility	Occupancy, Ambient Light for Daylight harvesting, 1-10 Volt Control Input
LED Components	SMD Mid-Power Lumiled 2835C series
Lens/Diffuser Choices	Snap-on Polycarbonate Diffuser or Lens
Photometrics	IES files available on request
Efficacy	188 Lumens/Watt
In-Situ Temperature Measurement Test (ISTMT)	44.3° C (L70 >200K hrs, L90 > 57K hrs)
Operating Temp Range	-30° F to + 130° F
Certifications	    
Standards	UL 1993, 1598, 1598B, 1598C, 8750, RoHS
DesignLights Consortium	 Check DLC QPL to confirm Models listed http://designlights.org/qpl/
Warranty	Ten Year Replacement Warranty covers LED Strips and Drivers
Rated Lifetime	100,000 hrs
Made-In-USA, BAA and BABA Compliant 	




RedBird Drivers

Constant Current, Dim-to-Zero Option

Model #	Watts	Lumens
RBD-9W-CC	9	1,710
RBD-14W-CC	14	2280
RBD-18W-CC	18	3,420
RBD-22W-CC	22	4180
RBD-28W-CC	28	5,320
RBD-36W-CC	36	6,840
RBD-44W-CC	44	8,360
Philips SS 95	95	18050
Philips SS 190	190	36,100



Optional Angle-Tilt for Hard-Mount



Kit Model # Designation for Ordering						Model #
Strip Length	-	Strips per Kit	-	Power	-	CCT: 3500K, 4100K, 5000K
S4	-	2	-	28W	-	41K
(4' strip)						
S2	-	3	-	22W	-	35K
(2' strip)						
				CC Driver		
						Example Kit Name
						S4-2-28W-41K
						S2-3-22W-35K

